

Do-It-Yourself Arcade Controls

Under construction.

Many DIY or prebuilt arcade cabinets, cocktail tables, and bartops use an **encoder/controller board** to connect joysticks and buttons to the system running Batocera (for example, Ultimarc I-PAC devices or JAMMASD boards). These boards often present themselves as a **keyboard**, meaning button presses generate keyboard **KEY_** events.

Keyboard-style input isn't always ideal for emulation, because some systems and configurations expect a **gamepad/controller** device (for example, devices recognized as joystick/gamepad input rather than a keyboard). Some boards (like certain Ultimarc models) can be switched to appear as **DInput/XInput** controllers, but cabinets often add another wrinkle: they may include dedicated buttons for cabinet functions like **Menu**, **Exit**, and **Pause**.

Normally, Batocera uses a **HOTKEY + ANOTHER BUTTON** combination to trigger actions like Menu, Exit, or Pause (see [Hotkey shortcuts](#)). With dedicated cabinet buttons, requiring an additional hotkey can be redundant.


Since Batocera v41, two tools help address these common cabinet needs:

- **KeyboardToPads**: Converts specific keyboard-style encoders into one or more **virtual controller** devices by remapping input events (so they behave like standard controllers in emulators).
- **Hotkeygen**: Listens for specific **KEY_/BTN_ events** from input devices and triggers Batocera hotkey actions (Menu/Exit/Pause, etc.) by emitting the configured key sequence (or running a command). This makes **dedicated cabinet buttons** work without requiring a separate hotkey button.

These tools can be used together: **keyboardToPads** can produce clean controller-style inputs, and **hotkeygen** can interpret selected button events as hotkey actions.

Gallery







Arcade machine seller respecting licences

Most premade arcade machines sellers are not respecting batocera and emulators licences.

Here is a list of 2 sellers respecting licences :

- <https://iconicarcade.com/>
- <https://recroommasters.com/>

Contextual Hotkeys

Contextual hotkeys are the way Batocera maps hotkeys to actions in emulators. For each emulator, the emulator hotkeys are referenced and mapped to Batocera hotkeys. The following is the list of hotkeys they may be help when configuring KeyboardToPads and Hotkeygen:

Batocera hotkey	Keyboard key equivalent
exit	KEY_EXIT
coin	KEY_EURO
menu	KEY_MENU
pause	KEY_PAUSE
reset	KEY_RESTART
files	KEY_FILE
save_state	KEY_SAVE
restore_state	KEY_SEND
next_slot	KEY_NEXT
previous_slot	KEY_PREVIOUS
rewind	KEY_REWIND
fastforward	KEY_FASTFORWARD
next_disk	KEY_VIDEO_NEXT
translation	KEY_SUBTITLE
bezels	KEY_FRONT

Batocera hotkey	Keyboard key equivalent
swap_screen	KEY_SCREEN
screen_layout	KEY_PRESENTATION
screenshot	KEY_SYSRQ
volumeup	KEY_VOLUMEUP
volumedown	KEY_VOLUMEDOWN
volumemute	KEY_MUTE
brightness-cycle	KEY_BRIGHTNESS_CYCLE

Using and Configuring Hotkeygen

Configuring Hotkeygen will allow you use dedicated cabinet buttons such Menu, Exit, or Pause without having use it in combination with a hotkey.

TIP: Using and configuring Hotkeygen and KeboardToPads assumes you know how to access Batocera at the terminal and access and manipulate files. If you are unfamiliar with how to do this, consult [Access Batocera Via SSH](#)

While Emulationstation is running, the hotkeygen `--list` command will return something similar to :

```
$ hotkeygen --list
Context [emulationstation]:
  exit-----> KEY_ESC
  menu-----> KEY_SPACE
  files-----> KEY_F1
# device /dev/input/event5 [Ultimarc I-PAC 4] (no Ultimarc_IPAC_4-
d209-430.mapping file found)
  KEY_PAUSE-----> pause
# device /dev/input/event3 [AT Translated Set 2 keyboard] (no
AT_Translated_Set_2_keyboard-01-01.mapping file found)
  KEY_PAUSE-----> pause
# device /dev/input/event23 [Xtension hotkeys] (no
Xtension_hotkeys-00-00.mapping file found)
  KEY_EXIT-----> exit-----> KEY_ESC
  KEY_MENU-----> menu-----> KEY_SPACE
  KEY_PAUSE-----> pause
```

This example response above tells you:

- The current context is `emulationstation`
- The hotkey “exit” will send the equivalent of the keyboard `KEY_ESC` (escape key)
- The hotkey “menu” will send the equivalent of the keyboard `KEY_SPACE` (space bar)
- The hotkey “files” will send the equivalent of the keyboard `KEY_F1` (F1 key)
- There are 3 devices are able to generate these events (via `KEY_EXIT`, `KEY_MENU`, and so on)
- There is no custom mapping file found for any of the 3 devices. The standard hotkeys will be applied.

Here is another example of context while running PS Portable emulator (`ppsspp`):

```
$ hotkeygen --list
Context [ppsspp]:
  exit-----> ['KEY_LEFTALT', 'KEY_F4']
  save_state-----> KEY_F3
  restore_state---> KEY_F4
  menu-----> KEY_F9
  pause-----> KEY_F9
  next_slot-----> KEY_F6
  previous_slot---> KEY_F5
$
```

You can also simulate the hotkeys from the command line. Within any context, for example, the hotkey “exit” will quit the game. It can be launched via the command:

```
hotkeygen --send exit
```

And when available, the following command will pause the emulator. With most emulators, the hotkeys menu and pause do the same:

```
hotkeygen --send pause
```

If you add the parameter `-debug`, you can get more details. For example, the command `hotkeygen --list -debug` will give you the paths used to customize your contexts.

Extend hotkeygen config

Default hotkeygen config is available in `/etc/hotkeygen`. Files `common_context.conf` and `default_context.conf` can be created in the folder `/userdata/system/configs/hotkeygen`. If any, they will be merged with the default config.

- `common_context.conf` is used to define hotkeys always available, whatever the context, like taking a screenshot
- `default_mapping.conf` is used to define which keys set which action. In theory, you don't need to customize this file.

You need to restart the hotkeygen service so that any update on these file is taken.

Using KeyboardToPads to Convert Keyboard Controllers to Gampads/Controllers

Keyboard-style input isn't always ideal for emulation, because some systems and configurations expect a gamepad/controller device. KeyboardToPads can convert these keyboard encoders to one or more virtual gamepads/controllers.

Batocera can detect, and has prebuilt configuration files for, some of the more common keyboard encoders.

To check whether there is a prebuilt configuration file for your device, you can run: `keyboardToPads --search`. Below is an example output:

```
$ keyboardToPads --search
device /dev/input/event3 : "Ultimarc I-PAC 4"
  config file name : UltimarcIPAC4.vd209.p0430.yml
  system config found at
/usr/share/keyboardToPads/inputs/UltimarcIPAC4.vd209.p0430.yml
  you can create a custom config at
/userdata/system/configs/keyboardToPads/inputs/UltimarcIPAC4.vd209.p0430.yml
. Take example on files in /usr/share/keyboardToPads/inputs.
```

It will display your pads if any, and the file you need to create in order to customize it.

Files are in yaml format.

There are some file samples in `/usr/share/keyboardToPads/inputs`.

Example :

```
# Xtension 2 Player Plus
target_devices:
- name: Xtension 2P Player 1
  type: joystick
  mapping:
    "key:up": "abs:hat0y:-1"
    "key:down": "abs:hat0y:1"
    "key:left": "abs:hat0x:-1"
    "key:right": "abs:hat0x:1"
    "key:leftshift": "btn:south"
    "key:enter": "btn:south"
    "key:z": "btn:west"
    "key:leftctrl": "btn:west"
    "key:leftalt": "btn:north"
    "key:space": "btn:tl"
    "key:x": "btn:tr"
    "key:c": "btn:start"
    "key:l": "btn:start"
    "key:v": "btn:select"
    "key:5": "btn:select"
- name: Xtension 2P Player 2
  type: joystick
  mapping:
    "key:r": "abs:hat0y:-1"
    "key:f": "abs:hat0y:1"
    "key:d": "abs:hat0x:-1"
    "key:g": "abs:hat0x:1"
    "key:w": "btn:south"
    "key:i": "btn:west"
    "key:a": "btn:west"
    "key:s": "btn:north"
```

```

    "key:q": "btn:tl"
    "key:k": "btn:tr"
    "key:j": "btn:start"
    "key:2": "btn:start"
    "key:1": "btn:select"
    "key:6": "btn:select"
- name: Xtension hotkeys
  type: hotkeys
  mapping:
    "key:tab": "key:menu"
    "key:p": "key:pause"
    "key:esc": "key:exit"
    ["key:1", "key:v"]: "key:exit" # exit from combination player 1 select
+ player 2 select, require batocera 43
    ["key:c", "key:space"]: "key:1" # player 2 select from combination
player 1 start+tl, require batocera 43

```

In that example, the controller is split into 3 virtual devices: 2 pads and 1 hotkey device.

Warning, don't put "PAC" in the name of your virtual names, otherwise, it will conflict.

Note that once you've created this file, you just need to unplug and replug the device so that it is taken into account.

Note that the naming and mapping of the device create a virtual pad, but you will have to configure it via Emulationstation as usual for any controller, as it wouldn't be in our database yet). (**Main Menu → CONTROLLER & BLUETOOTH SETTINGS → CONTROLLER MAPPING**) If you don't do this, it will not work in an emulator.

The name of the first virtual pad is Xtension 2P Player 1. Rename Xtension 2P Player 1 & 2 to the name of your controller. Its type is "joystick". Possible types are "joystick" for pads, and "hotkeys" for hotkeys.

mapping is a key-value association table to convert each key from the real device into the virtual pad. You can assign two or more physical keys to a single pad button.

You can use the following command to find the input keys :

```
evsieve --input /dev/input/event3 --print
```

You may also want to use btn:tl2 and btn:tr2 (left and right second triggers) depending on your context.

Troubleshooting


In case of error, you can try to run this command (with the event number corresponding to your setup):

```
keyboardToPadsLauncher /dev/input/event3 run
```

Before batocera 41

JammASD

This guide will help you to use your original arcade cabinet controls (sticks and buttons) under Batocera. The simplest way actually, is to use a **JammASD controller**.



For the moment, this controller (used to send VGA signal, sound, and control information to your JAMMA connector) is not known by EmulationStation, but a few tips can help you to use Batocera in your original cabinet.

JammASD and Emulation Station

Under EmulationStation, JammASD's controls are considered as a keyboard, and it's not the easiest way to configure 2 players controllers.

So, you have to change your JammASD drivers into X-Arcade drivers to use all your arcade panel.

1. Connect to Batocera using SSH
2. Type:

```
ls /dev/input/by-id
```

You will see this interface : *usb-ASD_JammASD_Interface_ASD275D-if01-event-kbd*

```
touch /userdata/system/configs/xarcade2jstick/usb-  
ASD_JammASD_Interface_ASD275D-if01-event-kbd
```

3. Reboot your Batocera

Now, you only have to edit your controls under EmulationStation menu. Then, your arcade panel will be known as *Xarcade-to-Gamepad Device 1* and *Xarcade-to-Gamepad Device 2*

Note: With this tip, it's possible now to have START P1 + A to credit your arcade games ^^

Ultimarc

This instructions are for Batocera 5.24 or later, they are dedicated to [Ultimarc's line of control interfaces](#) (including I-PAC, J-PAC, A-PAC, Mini-PAC, Opti-PAC, U-HID and more) and X-Arcade USB Controllers.

TL;DR: If your encoder is any model of I-PAC or Mini-PAC, press and hold the buttons corresponding to Start1+P1SW2 for ten seconds. If you're lucky, your controller is now a plug 'n play USB controller you can [configure like any other controller](#) in batocera. That's it. You're done. Go play some games 😎

If nothing happens or you want to know more, keep reading.

The above will only work with Ultimarc's encoders (they call them control interfaces) made from 2015 on and equipped with Firmware version 50 or higher. You can check what you have with the software they offer [on their website](#). **This is important as flashing your pre-2015 encoder with the new firmware will brick it!** If your board is new enough, but your firmware isn't, you can update with the same tool. Read the information on their page under **“Multi-Mode”** to learn about the different modes and what you can do with them. The instructions above will make your controller run in Mode 2, which should be fine for most users. What this means is that instead of being recognised as a USB keyboard, your controller will now be recognized as a D-input game controller and you won't need to do any of the steps below.

If your Ultimarc encoder doesn't offer this functionality, you don't want to upgrade the firmware or you are using an X-Arcade controller, read on.

Xarcade2jstick has been patched to support keyboard encoders. You may have to reconfigure a few keys of your encoder as, sadly, x-gaming X-Arcade devices didn't map as usual mame controllers.

Do not change the key mappings of your I-PAC or Mini-PAC as it is unnecessary, but the following procedure only applies if your encoder is in keyboard mode, which is the default mode when they leave the factory.

Configuring your keyboard encoder

Follow these steps :

- login to your Batocera box locally or through SSH
- find your encoder's device name with `ls /dev/input/by-id`. Usually, there is a trailing kbd in the event name. For example : `usb-Ultimarc_IPAC_2_Ultimarc_IPAC_2_9-if01-`

event - kbd

PLEASE NOTE: a single encoder can have multiple possible names, so try all of them
 For example: usb-Cypress_I-PAC_Arcade_Control_Interface-event-kbd → works
 usb-Cypress_I-PAC_Arcade_Control_Interface-if01-event-kbd → doesn't work

- Now remount / as read-write mount -o remount,rw /
- Create an empty file that has the same name of your keyboard device found 2 steps above touch
 /usr/share/batocera/datainit/system/configs/xarcade2jstick/devicename.
 With the previous example : touch
 /usr/share/batocera/datainit/system/configs/xarcade2jstick/usb-Ultimarc_IPAC_2_Ultimarc_IPAC_2_9-if01-event-kbd
- Edit batocera.conf and set controllers.xarcade.enabled=1 (it should already be set by default but check it)
- Save your modifications through SSH batocera-save-overlay
- Reboot by typing reboot

Now all your keys should be usable, that is for each player : 4 directions joystick, select, start, hotkey, A, B, X, Y, L1 and R1.

For now it is not possible to attribute more buttons like L2, R2, L3 or R3

You must now configure both the controllers in the Controller Configuration menu and also associate the right controller to player 1 and 2.

Since Batocera **v34**, [Ultimarc](#) has been included. [Read more here](#).

Troubleshooting

The entire article is under construction but this part is *especially* under construction.

I use Dragonrise encoders and player 1 and player 2's inputs are swapped

For Batocera 40 and newer, the fix has been reported as not being necessary any longer, but this was an issue in previous versions.

Make sure they are all wired exactly the same, each button going to the same USB encoder.

If that's not working or is impossible to do due to your setup's requirements, it's possible to work around by using a USB quirk. Add the following onto the end of your boot line (on Raspberry Pi images, this is at /boot/uEnv.txt, x86_64 users can refer to [here](#)):

```
usbhid.quirks=0x0079:0x0006:0x040
```

It's added onto the end of the line, not on a new line. For instance, your boot line might end up looking like this:

```
APPEND=label=BATOCERA rootwait quiet loglevel=0 console=ttyAML0,115200n8
```

```
console=tty3 vt.global_cursor_default=0 usbhid.quirks=0x0079:0x0006:0x040
```

I have a two devices that are recognized as mice and I have to reconfigure them every launch

Arcade trackballs and spinners are handled as mouse devices.

The problem comes from the way newer versions of RetroArch recognize mouse devices, by ID instead of name. The ID that they can have is thus unpredictable, resulting in configs (such as `retroarchConfig['input_player1_mouse_index'] = "Barcode Reader Mouse"`) no longer working.

For now, this can be worked around using a script to automatically log and change the ID as appropriate. Save it to `/userdata/system/configs/emulationstation/scripts/game-start/mouse-fix.sh` and mark it as executable with `chmod +x /userdata/system/configs/emulationstation/scripts/game-start/mouse-fix.sh`:

[mouse-fix.sh](#)

```
#!/bin/bash

# NAME OF DESIRED MOUSE INPUT
# Can be found via the RetroArch log file or by running 'evtest'
mouse_name="Combined Analog Arcade Controls"

# RetroArch log file must be enabled for this to work
batocera-settings-set global.retroarch.log_dir
"/userdata/system/logs/retroarch"
batocera-settings-set global.retroarch.log_to_file true
batocera-settings-set global.retroarch.log_to_file_timestamp false

# Read the mouse index values from the last RetroArch log file
# and update the config for the next time RetroArch is run
# NOTE: Using '~' as a sed delimiter as some device names include the
# traditional '/' delimiter
# NOTE: Pipe to 'head -1' to return the index of the first matching
# device, as some devices expose multiple inputs
mouse_index=$(sed -En "s~.*Mouse.* #(.*) : \"$mouse_name\".*~\1~p"
/userdata/system/logs/retroarch/retroarch.log | head -1)
if [[ -z "$mouse_index" ]]; then
    mouse_index=0
fi
batocera-settings-set global.retroarch.input_player1_mouse_index
$mouse_index
```

You may need to launch a game twice in order for it to have an effect.

Keep updated by watching this space: <https://github.com/libretro/RetroArch/issues/7638>. Original forum post describing this issue and its workaround:

<https://forum.batocera.org/d/6652-being-able-to-use-trackball-and-spinner-using-per-mouse-index>

Batocera may make the workaround process easier in the future by the inclusion of evsieve.

Standalone MAME has its own mechanism for enabling spinner, trackball, and other mouse devices. In **ADVANCED GAME OPTIONS**, select **MAME** as the emulator, then choose **ENABLE MOUSE > ENABLED**.

From:

<https://www.wiki.batocera.org/> - **Batocera.linux - Wiki**

Permanent link:

<https://www.wiki.batocera.org/diy-arcade-controls?rev=1771986472>

Last update: **2026/02/25 02:27**

